



**S3 CI SRC**  
**EN ISO 20345:2011**  
**35 to 48**



**LINK-ESD**



- **Water-repellent full-grain leather**
- **PU/PU sole by BASF®**
- **ESD / Dissipative**
- **Polymer toe cap type B and midsole no metallic**

- ❖ Rangers style outdoor incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity).
- ❖ Water-repellent full-grain leather upper, pull-up finish, thickness 1,8 / 2,0 mm. **Excellent impermeability**, no water crossing after 7h test. Very good breathability (evacuation of sweating well above normative requirements).
- ❖ Scuff-resistant protective reinforcement to heel and PU reinforcement to the front of the sole.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ TPU reinforcement for better protection of the malleoli.
- ❖ Padded and lined leather tongue for instep protection with side bellows to keep out dust and dirt.
- ❖ Lace up with five pairs of no metallic eyelets and two pairs of **Quick Lio**. Laces 150 cm.
- ❖ Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a **soft BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESDTM system**, an innovative multi-contact, static electricity dissipater. (Patent pending).
- ❖ Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test ≥ 4mm in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ Stab-resistant structural insole and liner in **FleXtane™ By Jallatte ESD**, in compliance with standard **22568-4 : 2021**, antistatic, **100% composite**. Sewn directly onto the upper and covering **100% of the foot for total protection**.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ Insole **PU / PU de BASF®**, design outdoor, excellent slip resistance.



**Slip resistance tests results** EN Standard :  
EN ISO 20345 : 2011 **Requirement SRC (SRA+SRB)**

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,43** (>0,32) – On the heel **0,31** (>0,28)

**SRB** Test ground steel/lubricant : glycerine  
On flat **0,28** (>0,18) – On the heel **0,20** (>0,13)

- BExtremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.



Weight	Gross weight (42) : 1859 g / Net weight (42) : 1550 g
Size	35 à 48
Packaging	5 paires
Box shoes (mm)	337 x 328 x 135
Cartons (mm)	625 x 425 x 343

