



**S2 SRC**  
**EN ISO 20345:2011**  
**35 to 48**



ASEPTANE



Link-ESD



- Microfiber Aseptane™ .
- PU/PU sole by BASF®
- ESD / Dissipative
- Polymer toe cap type B

- ❖ Safety shoe type loafer incorporating **MAXI-Soft Duo™** anti-fatigue technology designed for work stations that require standing for long periods (Upright or sustained activity)..
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- ❖ White **Aseptane™** upper with microfiber resin combines optimal breathability and unmatched watertightness.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Padded tongue for good instep protection, combined with two side bellows to prevent any dirt from getting into the boots.
- ❖ Padded ergonomic collar in compact flexible foam, lined for extra comfort and better ankle and Achilles tendon protection.
- ❖ Snug fit thanks to elastic band underneath protective tongue.
- ❖ Perforated insole for enhanced comfort : **MAXI-Soft Duo™** composed of a **soft BASF® Dynamic PU** midsole with heat sensitive memory foam and a maximum size **BASF® Elastopan insert** that improves weight distribution by reducing pressure points and absorbs and relieves body stress associated with a prolonged standing working position and when walking. Anatomical, breathable and fitted with the **Link ESDTM system**, an innovative multi-contact, static electricity dissipater. (Patent pending).
- ❖ Ergonomic shoe, with broad synthetic polymer toe cap **Springtane-B™**. Impact resistance to 200 Joules. Minimum height after test  $\geq 4\text{mm}$  in relation to the Type A toe cap in accordance with Standard 22568-2 : 2021.
- ❖ Heel stiffener to reinforce the heel seat.
- ❖ **BASF® PU / PU sole** with an urban sport design, linear profile and excellent slip resistance.



**Slip resistance tests results** EN Standard :

EN ISO 20345 : 2011 Requirement **SRC** (SRA+SRB)

**SRA** Test ground : ceramic / lubricant : water and detergent  
On flat **0,62** (>0,32) – On the heel **0,48** (>0,28)

**SRB** Test ground steel/lubricant : glycerine  
On flat **0,23** (>0,18) – On the heel **0,19** (>0,13)



- BExtremely light and flexible support base.
- Constant energy return over the entire surface.
- Reduced feeling of fatigue due to posture.
- Relief that facilitates the evacuation of fluids.

|                |   |                 |                 |                 |
|----------------|---|-----------------|-----------------|-----------------|
| Weight         | Gross weight (42) : 1316 g / Net weight (42) : 1100 g |                 |                 |                 |
| Size           | 35 to 39  | 40 to 42        | 43 to 45        | 46 to 48        |
| Packaging      | 5 pairs   | 10 pairs        |                 | 5 pairs         |
| Box shoes (mm) | 306 x 192 x 114                                       |                 | 340 x 210 x 133 |                 |
| Cartons (mm)   | 590 x 210 x 320                                       | 590 x 410 x 320 | 685 x 423 x 347 | 695 x 227 x 366 |

