

Work clogs for professional use

(No toe cap, no anti-perforation)

J-PRO
347



JOJO208 JALDEREK ESD

EN ISO 20347 : 2012 OB A E WRU FO SRC
35 to 48



0%
METAL

ASEPTANE

Link-ESD



- ❖ Soft and lightweight safety clog with no toe cap or anti-perforation sole designed with anti-fatigue technology. Upper and sole assembled in France. White and grey.
- ❖ Safety shoe protecting the electronic devices against electrostatic discharge phenomena. Electrostatic dissipative shoes ESD Environmental Class II tested according to **EN 61340-4-3** and **EN 61340-5-1**.
- ❖ White **Aseptane™** upper with microfiber resin combines optimal breathability and unmatched watertightness.
- ❖ Upper lined in breathable **3D Surf** mesh with honeycomb structure to improve the peripheral ventilation of the foot, dries out rapidly.
- ❖ Top of instep is padded for enhanced comfort.
- ❖ Elasticated strap fastening for easier adjustment and better grip of the foot. Strap can be folded over the top of the foot and removed using the popper system on the side.
- ❖ **Soft+ Gel** footbed made of **BASF Dynamic polyurethane** with heat sensitive memory foam and acts over the entire surface of the foot, cushions pressure points, improves weight distribution and shock absorption caused by impact with the ground. Anatomical, breathable and fitted with the **Link ESD™** system, an innovative multi-contact static electricity dissipater (Patent pending).
- ❖ This is a **DGUV 112-191** certified model, with the option of swapping the hygienic insole provided for a **SECOSOL®** orthopaedic insole.
- ❖ Little heel stiffener for good holding of the foot in the shoe.
- ❖ Innovative **J-energy™** sole in bi-ingredient PU / and **BASF Infinergy® E-TPU** (Expanded Thermoplastic PolyUrethane) insert, with a remarkable capacity to reproduce more than 55% of the **energy accumulated** while walking in order to reduce fatigue and to prevent RSIs to the legs.



Slip resistance tests results	
EN Standard : EN ISO 20345 : 2011 Requirement SRC (SRA+SRB)	
SRA Test ground : ceramic / lubricant : water and detergent	
On flat 0,62 (>0,32) – On the heel 0,48 (>0,28)	
SRB Test ground steel/lubricant : glycerine	
On flat 0,23 (>0,18) – On the heel 0,19 (>0,13)	

- Outsole in Polyuréthane.
- E-TPU insert at low density of 0.25.
 - As elastic as rubber but lighter.
 - High resistance to abrasion and stretching.
 - Good chemical resistance.
 - Long-term durability in a wide temperature range.
 - **Dynamic performance in 3 phases: Shock Absorption - Accumulation of energy - Dynamic Return**



Weight	Gross weight (38) : 856 g / Net weight (38) : 640 g			
Size	35 to 39	40 to 42	43 to 45	46 to 48
Packaging	5 pairs	10 pairs		5 pairs
Box shoes (mm)	306 x 192 x 114		340 x 210 x 133	
Cartons (mm)	585 x 199 x 315	585 x 395 x 315	680 x 425 x 350	680 x 215 x 350